

Spectrum Cutting Solutions Pvt Itd

Product Data Sheet

<u>"SP-DD-15</u>

Product Description:

"SP -DD-15" is Rust Preventive Additive Package specially designed with blend of film forming material, corrosion inhibitor, and selected Double Oxidized Waxes to enhance the performance in Salt spray & Humidity Atmosphere.

Typical Properties:

- 1) Color
- 2) Appearance
- 3) Acid value
- 4) 10%solubility in MTo

Key performance:

- 1. Excellent Corrosion protection.
- 2. Excellent Dewatering properties.
- 3. Cost Effective
- 4. Good protection in Salt Spray & Humidity Atmosphere

Guideline Formulations:

Raw material	RPO (formulation)
SP-DD-15(HEAT AT 80DEG)	15
МТО	82.5
BUTYL CELLOSOLVE	2.5
Total	100

Result of RPO

Properties	Result
Salt Spray Test(ASTM B-117)	72 hrs
Dewatering	Passes
De-Emulsification	Passes
Humidity (ASTM D1748)	60days

Flamingo, Empire, 'A' Wing, Flat No 502, Survey No. 22, Behind Maratha Mandir Near Pristine Fontana Bldg., Bavdhan (Khurd), Pune -411021, Maharashtra info@spectrumcspl.com www.spectrumcspl.com

- : Hazy Dark Brown.
- : Liquid.
- : Max 20. Mg KoH/gm
- : Bright & clear



Spectrum Cutting Solutions Pvt Itd

Dosing :

15%

Storage condition:

Store inside warehouse, Temperature condition 30°C to 35°C

Avoid water collecting on barrel top,

Special instruction

For better Solubility Heat at 80-90 Deg

Shelf life :

6 month Form Date of manufacturing.

Pack size :

50 kgs HDPE Carboy, 200kgs HDPE Drums

For Health & safety please refer MSDS

Guidance information is given as per our knowledge.