



Spectrum Cutting Solutions Pvt Ltd

Product Data Sheet

“SP-SSOPW”

Product Description:

“SP -SSOPW” is Rust Preventive Additive Package specially designed with blend of film forming material, corrosion inhibitor, and selected Oxidized Waxes to enhance the performance in Salt spray & Humidity Atmosphere.

Typical Properties:

- | | |
|-------------------------|---------------------|
| 1) Color | : Hazy Dark Brown. |
| 2) Appearance | : paste |
| 3) Acid value | : Max 20. Mg KOH/gm |
| 4) 10%solubility in MTO | : Bright & clear |

Key performance:

1. Excellent Corrosion protection.
2. Excellent Dewatering properties.
3. Cost Effective
4. Good protection in Salt Spray & Humidity Atmosphere

Guideline Formulations:

Raw material	RPO (formulation)
SP-SSOPW(HEAT AT 80DEG)	20
Sn 500 gr i	20.0
MTO	57.5
BUTYL CELLOSOLVE	2.5
Total	100

Result of RPO

Properties	Result
Salt Spray Test(ASTM B-117)	200 hrs Passes
Acid Fume test in 18% conc HCl	72 hrs Passes
Dewatering	Passes
De-Emulsification	Passes
Humidity (ASTM D1748)	60days



Spectrum Cutting Solutions Pvt Ltd

Dosing :

20%

Storage condition:

Store inside warehouse, Temperature condition 30°C to 35°C

Avoid water collecting on barrel top,

Special instruction

For better Solubility Heat at 80-90 Deg

Shelf life :

6 month Form Date of manufacturing.

Pack size :

50 kgs HDPE Carboy, 200kgs HDPE Drums

For Health & safety please refer MSDS

Guidance information is given as per our knowledge.